

Tipping kit to suit a Truck with an 18 Speed Roadranger Gearbox, a 5m tipping Body & Trailer Coupling

Tipping Kit Inclusions



3 Stage Cylinder
Displacement Type
Hard Chromed
Mounting Brackets incl.

Lifts 28t to 51° over a 300mm Overhang.

P/N: S2-55BT-3-4200

18 Speed Roadranger combination
250 Nm PTO torque
65 Lpm @ 1000rpm Pump
Cont: 3200 psi, 1800 rpm
P/N: PPK-HCAR




120 Lpm twin spool tip valve
Pneumatic control
2500 psi relief setting
Max: 4000 psi
P/N: OP20/2TT



2 Pneumatic Cab Controls
PTO engagement switch on 1 control
6mm Nylon air fittings
P/N: AFH-400-03-332



90L steel oil tank
2 Port Options 1-1/4" BSPP c/w Plug
Bolt on inspection plate
Filler Breather & Site Glass
Provision for filtration
P/N: ACC-T90L



25 Micron return line filter
Tank top mounted c/w male nipple
300 Lpm
Paper Element
P/N: RTIR-10-25



1-3/4" Rear Hinge Kit
2x Chassis Brackets
4x Body Brackets
Collars, grease nipples and bar
P/N: HG1-3/4




6 Line Nylon air kit
Air fittings
Suction Elbow
Port fitting adaptors



Note:
Surcharge Options include alloy oil tank, 160 Lpm tip valve,
PTO variation and additional air switch.

NZ 0800 22 55 69
AU 1800 22 55 69
www.transporthydraulics.com
sales@transporthydraulics.com

Quote Ref:
Date:
NZ\$



THS

TRANSPORT
HYDRAULIC
SOLUTIONS

INNOVATION IN MOTION

www.transporthydraulics.com

